



SMART DESIGNS COME FROM SMART SOLUTIONS.



NESTAFLEX r2(

GRAVITY ROLLER CONVEYOR

Designed to expand, contract and move easily, the Roller 200 is a self tracking, gravity roller conveyor that has a per lineal foot capacity of 200 pounds! This unit is engineered to handle odd shaped cartons, drums, pails and in low to medium volume applications. Four point leg connection is the strongest in the Industry!

SPECIFICATIONS



The ALL-STEEL construction provides unmatched structural integrity, whether the conveyor is extended, contracted or

configured in simple or compound curves. Adjustable inner legs vary height to achieve gravity flow. The Roller 200 is the choice for use in a variety of applications, packaging areas, assembly lines and in low to medium volume shipping and receiving departments. Call us today to learn more at 800.669.1501 or visit the website at www.flexmh.com.

Model	Width (inches)	Contracted Length	Extended Length	Leg Sets (per unit)	Shipping Weight (lbs)
RLR18008S	18	2' 8"	8' 6"	3	185
RLR18024S	18	7'0"	23' 2"	7	415
RLR18040S	18	12' 5"	41'6"	12	740
RLR24008S	24	2'8"	8' 6"	3	210
RLR24024S	24	7'0"	23' 2"	7	470
RLR24040S	24	12' 5"	41' 6"	12	835

Example models lengths and widths. Please consult factory for a full list of options.

NESTAFLEX RLR STANDARD FEATURES AND OPTIONS

CONVEYOR FORMATS

Available in 18" and 24" and 30" widths. Lengths can be tailored to meet your specific application.

HEIGHT ADJUSTMENT

Standard adjustable heights from 28" to 36". Other height adjustments available.

HEAVY DUTY CASTERS

Standard 5" x 1¹/₂" swivel casters with steel brakes on ends.

LEGS

Zinc plated, heavy duty leg supports and 1 1/4" steel tubing featuring double, welded cross members for added strength.

BOX STOP/HANDLE

Retractable package stop serves also as an ergonomic handle.

SIDE LINKS

Conveyor side links are made of 7 gauge steel.

COUPLERS

Couplers are standard. Optional universal connectors are available to couple to other extendable convevor brands.

Flexible Material Handling

ROLLERS

Galvanized steel rollers with sealed ball bearings and spring loaded axles. Standard axle centers are 5¹/₄", 4" and 3" available for smaller cartons.

WARRANTY

24 month factory warranty.

SMART SOLUTIONS™ .flexmh. **W** W \// C 0 800-669-1501